



SAFETY DATA SHEET UGLOSS-AF PART 1

SECTION 1: IDENTIFICATION

PRODUCT NAME: UGLOSS-AF PART 1
UCI NA LLC.
P.O. BOX 826
ROYAL OAK, MI 48068

PRODUCT INFORMATION AND SDS: 800-826-2848
EMERGENCY PHONE: CHEMTREC 800-424-9300

REVISED DATE: 12/5/2021

SECTION 2: HAZARDOUS IDENTIFICATION

Hazard Overview

Flammable liquid category 3, Specific target organ toxicity – single exposure category 3, Acute oral toxicity category 4, Skin corrosion/irritation category 2, Serious eye irritation category 2A, Acute toxicity inhalation category 4, Acute Toxicity skin category 4, Specific target organ toxicity repeated exposure category 2 Acute hazard to aquatic environment category 3

Label Elements

Flame, Health Hazard, Exclamation Mark



Label Elements

Warning: Flammable liquid and vapor.
Warning: May cause respiratory irritation
Warning: Harmful if swallowed
Warning: Causes skin irritation
Warning: Causes serious eye irritation
Warning: Harmful if inhaled
Warning: Harmful in contact with skin.
Warning: May cause damage to organs (auditory system) through prolonged or repeated exposure.
Harmful to aquatic life.
Precautionary statements:
P102 Keep out of reach of children.
P103 Read label before use
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P260 Do not breathing dust/fume/gas/mist/vapours/spray
P271 Use only outdoors or in a well-ventilated area.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment. Response
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.
P370 + P378 In case of fire: Use Foam, alcohol foam, CO2, dry chemical, water fog for extinction.
P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.
P312 If Inhaled, Call a POISON CENTER or doctor/physician if you feel unwell.
P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.
P330 Rinse mouth.
P302 + P352 IF ON SKIN: wash with plenty of soap and water.
P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 IF eye irritation persists: Get medical advice/attention.
 P314 Get medical advice/attention if you feel unwell.
 Storage:
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P233 Keep container tightly closed.
 Disposal:
 P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws
 Other Non-classifiable potential hazards
 Carcinogenicity category 2, (Ethyl benzene at less than 17% in a study done by the NTP was determined to not be carcinogenic.)

HMIS Hazard Classification HEALTH: 2 FLAMMIBILITY: 3 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

Potential Health effects
 EYES: May cause corneal damage if left untreated which is slow to heal but usually reversible.
 SKIN: May cause irritation or allergic response. May cause defatting, dryness, cracking, rash or redness or dermatitis.
 SKIN ABSORPTION: Solvents can penetrate the skin causing effects similar to those for acute inhalation symptoms.
 INGESTION: Can cause irritation to the digestive tract including sore throat, abdominal pain, nausea, vomiting and diarrhea. Vomiting may Cause Aspiration of solvents resulting in chemical pneumonitis. INHALATION health risks and symptoms of exposure: Solvent vapors are irritating to the eyes, nose and throat and respiratory tract resulting in dryness of the throat and tightness in the chest. Other symptoms include headache, nausea, narcosis, fatigue and loss of appetite.

Health hazards (acute and Chronic)
 Chronic Exposure to organic solvents has been associated with various neurotoxic effects including brain damage, nervous system damage or death. Prolonged vapor contact may cause conjunctivitis. Chronic inhalation may also include loss of memory, loss of intellectual ability and loss of coordination. Corneal damage is possible but usually reversible. Repeated Exposure to solvents can cause anemia, liver abnormalities, kidney damage or cardiac abnormalities.

Additional Carcinogenicity Information
 MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
 Respiratory conditions or other allergic response.
 CARCINOGENICITY
 OSHA: NO NTP: NO IARC: YES
 ADDITIONAL CARCINOGENICITY INFORMATION:
 May Contain Ethyl Benzene (IARC possible carcinogen)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT | CAS NO. | OSHA PEL | ACGIH TLV | OSHA STEL | WEIGHT % |
|---|--------------------|------------|------------|------------|----------|
| POLYESTER POLYOL | NJTSRNS0001C | NONE | NONE | NONE | 40-70 |
| Siloxanes and silicones, di-me reactions products with silica (non-hazardous) | 67762-90-7 | NONE | NONE | NONE | 0.1-1 |
| siloxanes and silicones, di-methyl (non-hazardous) | 63148-62-9 | NONE | NONE | NONE | 0.1-1 |
| *XYLENE | 1330-20-7 | 100PPM | 100PM | 150PPM | 14 |
| *ethyl benzene (as a component of xylene) | 100-41-4 | 100ppm | 100ppm | 125ppm | <2.0 |
| 2,6-Dimethyl-4-Heptanone | 108-83-8 | 25 ppm | 25 ppm | NONE | 0.1-1 |
| polyalkylene glycol | 9038-95-3 | NONE | NONE | NONE | 0.1-1 |
| 4,6-dimethyl-2-heptanone | 19549-80-5 | NONE | NONE | NONE | 0.1-1 |
| Dibutyltin Dilurate | 77-58-7 | 0.1mg / m3 | 0.1mg / m3 | 0.1mg / m3 | 0.1-1 |
| Cellulose Acetate Butyrate | 9004-36-8 | NONE | NONE | NONE | 0.1-1 |
| Methyl N-Amyl Ketone | 110-43-0 | 100 ppm | 50 ppm | NONE | 10-30 |
| 4-chlorobenzotrifluoride | 98-56-6 | NONE | NONE | NONE | 3-7 |
| Additive | NJTSRN 800963-5023 | NONE | NONE | NONE | 0.1-1 |
| Light stabilizer | TRADE SECRET | NONE | NONE | NONE | 0.1-1 |
| Benzotriazole Derivative, Branched Ester | TRADE SECRET | NONE | NONE | NONE | 0.1-1 |

SECTION 3 NOTES: *Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372. All components are on the TSCA list. Xylene Stel= 150PPM (ACGIH) Methyl N-Amyl Ketone Stel (ACGIH)= 100PPM.
 Note: Ingredients listed without percentages, the percentages are considered a trade secret.

SECTION 4: FIRST AID MEASURES

Eyes IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER, OCCASIONALLY LIFTING THE UPPER AND LOWER EYELIDS. CHECK FOR AND REMOVE ANY CONTACT LENSES. CONTINUE TO RINSE FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

Skin WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

| | |
|-------------------|---|
| Ingestion | DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CONSULT A PHYSICIAN. |
| Inhalation | REMOVE VICTIM TO FRESH AIR AREA AND ADMINISTER OXYGEN IF NECESSARY. CONSULT A PHYSICIAN IF NECESSARY. |

SECTION 5: FIRE FIGHTING MEASURES

| | |
|---|---|
| Suitable Extinguishing Media | FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG. |
| Special Fire Fighting Procedures | DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL ALL FIRE EXPOSED CONTAINERS WITH WATER. MINIMIZE CONTACT WITH MATERIAL. |
| Unusual Fire And Explosion Hazards | CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. SOLVENT VAPORS MAY BE HEAVIER THAN AIR. UNDER CONDITIONS OF STAGNANT AIR, VAPORS MAY BUILD UP AND TRAVEL ALONG THE GROUND TO AN IGNITION SOURCE WHICH CAN RESULT IN FLASH BACK TO THE SOURCE OF THE VAPORS. TOXIC VAPORS COULD BE EVOLVED FROM THE COMBUSTION OF THIS MATERIAL. |
| | FLAMMABLE LIMITS IN AIR, UPPER: NOT AVAILABLE (% by volume) LOWER: NOT AVAILABLE |
| | FLASH POINT: 100°F |
| | METHOD USED: SETA FLASH |

SECTION 6: RELEASE MEASURES

| | |
|--|--|
| Steps To Be Taken In Case Material Is Released or Spilled | REMOVE ALL SOURCES OF IGNITION AND VENTILATE THE AREA. WEAR APPROPRIATE PROTECTIVE EQUIPMENT SUCH AS VAPOR CARTRIDGE OR AIR SUPPLIED RESPIRATOR WHEN NECESSARY. DIKE AND ABSORB THE MATERIAL WITH ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. |
|--|--|

SECTION 7: HANDLING AND STORAGE

| | |
|--|--|
| Precautions To Be Taken In Handling And Storage | STORE IN COOL DRY AREA. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING THE TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING THE MATERIAL. PROPERLY LABEL ALL CONTAINERS. |
| Other Precautions | AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CANNOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF. SUPPLY APPROPRIATE VENTILATION OR ENGINEERING CONTROLS PRIOR TO USING THIS PRODUCT. |

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| | |
|---|---|
| Respiratory Protection | USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. USE A POSITIVE PRESSURE RESPIRATOR WHEN AIRBORNE CONCENTRATIONS ARE NOT KNOWN OR IF EXCEEDING TLV'S OR IF WORKING IN A CONFINED SPACE. ALWAYS CONSIDER THE HAZARDS FROM ALL COMPONENTS IN THE MIXED MATERIAL STATE. |
| Ventilation | EXHAUST VENTILATION SUFFICIENT TO KEEP THE AIRBORNE CONCENTRATIONS OF THE SOLVENTS AND OTHER HAZARDOUS MATERIALS BELOW THE TOXIC LEVEL CONCENTRATIONS. |
| Protective Gloves | IMPERVIOUS GLOVES – NEOPRENE OR RUBBER. |
| Eye Protection | SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS. IF THE ENVIRONMENT WARRANTS, A FULL FACE SHIELD SHOULD BE EMPLOYED. |
| Other Protective Clothing Or Equipment | WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS AN APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT. |
| Work Hygienic Practices | OBSERVE GOOD GENERAL HYGIENIC PRACTICES. SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES. |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|--|
| Appearance And Odor | LOW VISCOSITY LIQUID WITH KETONE SOLVENT ODOR. |
| Boiling Point Or Range | 279° TO 375°F |
| Vapor Density | NOT AVAILABLE |
| Specific Gravity | 1.0 |
| Evaporation Rate | NOT AVAILABLE |
| Solubility In Water | NEGLIGIBLE |
| Odor Threshold | N/A |
| pH | N/A |
| Melting Point | N/A |
| Freezing Point | N/A |
| Vapor Pressure | N/A |
| Auto Ignition Temperature | N/A |
| Decomposition Temperature | N/A |
| Partition Coefficient: n-octanol/water: | N/A |

SECTION 10: STABILITY AND REACTIVITY

| | |
|--|---|
| Stability | STABLE |
| Condition To Avoid (Stability) | AVOID EXCESSIVE HEAT OR OPEN FLAMES. THIS MATERIAL SHOULD NOT BE MIXED WITH PHOSPHOROUS CONTAINING MATERIAL OR OXIDIZERS. |
| Incompatibility (Material To Avoid) | CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND PHOSPHOROUS CONTAINING MATERIALS. |
| Hazardous Decomposition | CARBON MONOXIDE AND CARBON DIOXIDE. |
| Hazardous Polymerization | WILL NOT OCCUR. |

SECTION 11: TOXICOLOGICAL INFORMATION

| | |
|-----------------------|---|
| Component Data | <p>Component CAS# 9038-95-3: Acute oral toxicity LD50 = 5370 mg/kg (rat); Acute dermal toxicity LD50 = 21000 mg/kg (rabbit); Acute inhalation toxicity LC50 = 4670 ppm (rat); Skin irritation – slight irritation (rabbit); Eye irritation – mild irritation (rabbit)</p> <p>Component CAS# 108-83-6: Acute oral toxicity LD50 = 5800 mg/kg (rat); Acute dermal toxicity LD50 = 16000 mg/kg (rabbit); Acute inhalation toxicity LC50 = 2000 ppm (rat); Skin irritation – slight irritation (rabbit); Eye irritation – mild eye irritation (rabbit)</p> <p>Component Xylene: Inhalation LC50 26800ppm, Skin LD50 2000 mg/kg, Ingestion LD50 4.3 g/kg. Exposure may effect skin, eye, liver, kidney, nervous system, respiratory system and lungs. High concentrations may lead to nervous system effects. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal. Xylene may contain ethyl benzene, and toluene. Ethyl benzene has shown limited evidence of a carcinogenic effect.</p> <p>COMPONENT Ethyl Benzene: Acute Oral toxicity LD50: ca. 3500 mg/kg (rat); Acute inhalation LC50: 17.2 mg/l 4h (rat); Acute Dermal Toxicity: 17,800 mg/kg (rabbit); Skin Irritation rabbit Draize exposure time 24h – slightly irritating. Eye Irritation rabbit Draize – severely irritating. Sensitization dermal (human patch test) non-sensitizer. Repeated Dose toxicity 28 days inhalation NOAEL: 3.4 mg/l (rabbit). Mutagenicity Genetic Toxicity in Vitro: Ames: Negative (salmonella typhimurium, metabolic activation with/without). Carcinogenicity: Ethyl benzene was tested by inhalation exposure in mice and rats. In mice, there was an increased incidence of lung adenomas in males and liver adenomas in females. In male rats, there was an increased incidence of renal tubule adenomas and carcinomas. Two Studies of workers potentially exposed to ethyl benzene in a production plant and a styrene polymerization plant, showed no excess cancer incidence and no excess cancer mortality during a 15 year follow-up. Toxicity to Reproduction/Fertility: Inhalation (monkey, male) Reproductive effects have been observed in animal studies, In a generation study, inhalation (rat/female) NOAEL (parental): 100ppm NOAEL (F2): 100ppm. Developmental Toxicity/Teratogenicity rat, female, inhalation, gestation, daily, NOAEL (teratogenicity): 100ppm (maternal): 100ppm. Teratogenic effects seen only with maternal toxicity., Fetotoxicity seen only with maternal toxicity. Rabbit, female, inhalation, gestation, daily, NOAEL (teratogenicity) < 1000 mg/m3, NOAEL (maternal) < 1000 mg/m3.</p> <p>Component Dibutyltin Dilurate CAS# 77-58-7: ACUTE ORAL TOX (LD50,RAT) 3200.00 MG/KG. ACUTE DERMAL TOX (LD50,RABBIT) >2000 MG/KG (NO DEATHS). ACUTE INHAL TOX (LC50, RAT) >8.10 MG/L/1 HR. AMES TEST: NEG (ACTIVATED & NONACTIVATED) INDUST CHEMS SUCH AS THIS MATL W/ACUTE TOX VALUES SHOWN & WHOSE VAPS/MISTS ARE NOT LIKELY TO BE ENCOUNTERED BY HUMANS WHEN USED IN ANY REASONABLY FORESEEABLE MANNER WOULD NOT REQ TOXIC LABEL ACCORD TO U.S. DOMESTIC & INTERNATIONAL TRANSPORT REQS. IRRITATION DATA: SEV IRRITANT TO EYES OF RABBIT.</p> |
|-----------------------|---|

MOD IRRITANT TO SKIN OF RABBIT.

Component Cellulose Acetate Butyrate Ester CAS# 9004-36-8: Oral LD-50: (Rat): > 3,200 mg/kg (highest dose tested). Dermal LD-50: (Guinea Pig): > 1,000 mg/kg (highest dose tested). Skin Corrosion: (Guinea Pig, 24 h): slight. Skin sensitization: not a sensitizer.

Component CAS# 110-43-0: Oral LD 50 (rat): 1600 mg/kg; Oral LD50 (mouse) 730 mg/kg; Inhalation LC50 (rat) 2000-4000 ppm, 4 hr. Dermal LD50 (rabbit) 10206 mg/kg; Dermal LD50 (guinea pig) >16200 mg/kg; Skin irritation (Rabbit) – slight to moderate; Eye irritation (rabbit) slight; Skin sensitization (human) none

Component additive NJTSRN 800963-5023: Acute oral toxicity: LD50 rat>8,000,000 mg/kg; skin irritation rabbit – no skin irritation

Component(s) Light stabilizer CAS# Trade Secret and Benzotriazole Derivative, Branched Ester CAS# Trade Secret: Acute oral toxicity:LD50 / oral / rat: > 2,000 mg/kg (Based on components). Skin irritation: Not expected to be a skin irritant. (based on known component information). Eye irritation: Not expected to be an eye irritant. (Based on components). Skin irritation: Not expected to be a skin irritant. (based on known component information). Eye irritation: Not expected to be an eye irritant. (Based on components). Skin Sensitization: Not expected to cause sensitization. (based on known component information). Subchronic Toxicity: Information on: Benzotriazole Derivative, Branched Ester In a 14-day study, rats were administered the active ingredient at 0, 10, 100, or 1,000 mg/kg by gavage. The 100 and 1,000 mg/kg dose levels were found to cause elevated serum liver enzyme levels and enlarged livers. The no observable effect level (NOEL) was 10 mg/kg. In a 28-day study, rats were administered the active ingredient at 0, 2, 50, and 500 mg/kg by gavage. No treatment-related clinical or neurological signs of toxicity or mortalities were recorded. Treatment-related effects, including mild anemia and toxic effects in the liver, were seen. Slight activity of the thyroid gland was also recorded and considered a secondary response to the effects in the liver. The no observable effect level (NOEL) was 2 mg/kg. Information on: Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidinyl)ester, reaction products with tert-Bu hydroperoxide and octane In a 28-day study, rats were administered daily oral doses of 10, 100 or 1000 mg/kg/day. Males only in the 1000 mg/kg dose group exhibited a reversible, minor effect on prothrombin time, as well as effects on the formation and development of blood cells in the liver that were not totally reversed by the two-week recovery period. The no observable effect level (NOEL) was determined as 100 mg/kg in the males and 1000 mg/kg in the females. piperidinyl)ester, reaction products with tert-Bu hydroperoxide and octane Information on: Decanedioic acid, bis(2,2,6,6-tetramethyl-4-piperidinyl)ester, reaction products with tert-Bu hydroperoxide and octane. Genetic toxicity: Non-mutagenic (based on composition).

Component 4-chlorobenzotrifluoride CAS# 98-56-6: Oral Rat LD50 >6700 mg/kg. Inhalation rat LC50 (4 hr) = 4,370 ppm. Dermal Rabbit LD50 > 2,700 mg/kg. EYE IRRITATION DATA: In eye irritation studies, the compound was found to be slightly to moderately irritating. SKIN IRRITATION DATA: In skin irritation studies, the compound was found to be slightly to moderately irritating. SKIN SENSITIZATION DATA: No skin sensitization data are available on this material. SUBCHRONIC DATA: A 13-week inhalation study was conducted in rats exposed for 6 hours per day, 5 days a week at concentrations of 0, 10, 51, or 252 ppm. An increase in liver weights was seen in the high dose group. No macroscopic effects were noted. No adverse central nervous system effects were observed as measured by motor activity, functional observation battery, or neuropathology. In a separate study, rats were dosed daily via oral gavage for three months at 0, 10, 40, 150, or 500 mg/kg. Effects noted included initial decrease in body weight gain, decreased food consumption, and changes in biochemical parameters. Increases were noted in liver, kidney, and thyroid weights in both sexes in most treatment groups. Microscopic effects were also observed in these same organs. No overt physical signs of toxicity were observed during treatment. Effects similar to those described in the above two studies have also been observed in shorter inhalation and oral gavage testing. REPRODUCTIVE TOXICITY: In a two-generation reproduction study rats were exposed daily via oral gavage at doses of 0, 5, 15, and 45 mg/kg. Only limited reproductive effects were noted. TERATOGENICITY (birth defects): No teratogenicity data are available on this material. MUTAGENICITY: This material was found to be negative in the following in vitro mutagenicity studies: chromosomal aberration study, cell transformation assay, DNA repair deficiency assay, and the mouse lymphoma forward mutation assay. In the in vitro Ames test, the compound was generally found to be negative; however two strains at the high dose produced positive results. In the in vitro sister chromatid exchange test, the compound produced positive results. In the in vivo cytogenetic assay in rats, the compound was found to be negative.

SECTION 12: ECOLOGICAL INFORMATION

Component Data

Component Xylene: Acute Toxicity: Fish: Toxic 1 < LC/EC/IC50 < 10mg/l, Aquatic Invertebrates: Toxic 1 < LC/EC/IC50 < 10mg/l, Algae: Toxic 1 < LC/EC/IC50 < 10 mg/l. Mobility – floats on water. If it enters the soil it will be highly mobile and may contaminate groundwater. Oxidizes rapidly by photo-chemical reactions in air.

COMPONENT Ethyl Benzene: Biodegradation, Aerobic, 50%, Exposure time 28 days. Biochemical Oxygen demand (BOD) 5 days, 2.8% and 35 days, 1780 mg/g. Bioaccumulation: Cyprinus carpio (Carp), 15 BCF. Acute and Prolonged Toxicity to Fish LC50: 12.1 mg/l (fathead minnow, 96 h). Acute Toxicity to Aquatic Invertebrates EC50: 1.8-2.9 mg/l (water flea, 48 h). Toxicity to Aquatic Plants EC50: 4.6 mg/l (green algae, 72 h). Toxicity to microorganisms EC50: 130 mg/l (activated sludge microorganisms, 48 hr).

Component CAS# 110-43-0: BOD-5: 1770 mg/kg; BOD-20: 2000 mg/kg; COD: 2420 mg/kg. Acute Aquatic Effects: 96 hr LC50 (fathead minnow) 131 mg/l and 48 hr EC50 (daphnia) >90 mg/l (highest concentration tested)

Component 763-69-9: Possibly hazardous short term degradation products are not likely, however long term degradation products may arise. The product itself and its products of degradation are not toxic.

Component 4-chlorobenzotrifluoride CAS# 98-56-6: This compound is harmful to fish, Daphnia, and algae. Relatively

biodegradable. This substance is not expected to bioaccumulate. Insoluble in water; water volatility may be high. OTHER ECOTOXICOLOGICAL DATA: In a chronic fish study in *Pimephales promelas*, the NOEC and LOEC values were found to be 0.54 mg/l and 1.4 mg/l, respectively. ENVIRONMENTAL FATE DATA: In an anaerobic screening study, the substance was found to degrade 64% after 59 days. This substance is not expected to bioaccumulate based on an estimated bioconcentration factor (BCF) of 120.

SECTION 13: WASTE DISPOSAL

Disposal Methods DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAW.

SECTION 14: TRANSPORT INFORMATION

DOT NOT REGULATED
IMO/IMDG UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A Diglycidyl Ether Polymer), 9, PGIII, Marine Pollutant

SECTION 15: REGULATORY INFORMATION

Component Data Component CAS# 25068-38-6: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, WHMIS class D2B; Is on the New Jersey Right to Know list; is on the PA Right to Know List;
Component CAS# 68609-97-2: Considered a hazardous chemical; is on the TSCA list; is on the DSL Canada, Is on the New Jersey Right to Know list; is on the PA Right to Know List.
Component CAS# 14807-96-6 may contain Crystalline Silica (Silicon Dioxide) which is on the TSCA list. NTP list as a known human carcinogen, California proposition 65 list as a known carcinogen, Massachusetts Toxic Use Reduction Act

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available
See Section 1 for date of preparation

SECTION 1: IDENTIFICATION

PRODUCT NAME: UGLOSS-AF PART 2
UCI NA LLC.
P.O. BOX 826
ROYAL OAK, MI 48068

PRODUCT INFORMATION AND SDS: 800-826-2848
EMERGENCY PHONE: CHEMTREC 800-424-9300

REVISED DATE: 12/5/2021

SECTION 2: HAZARDOUS IDENTIFICATION

Hazard Overview

Flammable liquid category 3, Specific target organ toxicity single exposure category 3, Specific target organ toxicity following repeated exposure category 2, Respiratory sensitization category 1B, Skin corrosion/irritation category 2, skin sensitizer category 1B, Serious eye irritation category 2B, Acute toxicity inhalation category 4, Acute hazard to aquatic environment category 3, Chronic hazards to aquatic environment category 3

Label Elements

GHS Label Elements and Precautionary Statements: Flame, Health Hazard Exclamation Mark



Hazardous Statement

Warning: Flammable liquid and vapor
Warning: May cause respiratory irritation
Warning: May cause damage to organs (auditory) through prolonged or repeated exposure
Danger: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Warning: Causes skin irritation
Warning: May cause an allergic skin reaction
Warning: Causes serious eye irritation
Warning: Harmful if inhaled
Harmful to aquatic life
Harmful to aquatic life with long lasting effects
Precautionary statements:
P102 Keep out of reach of children.
P103 Read label before use
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P271 Use only outdoors or in a well-ventilated area.
P260 Do not breathe dust/fume/gas/mist/vapours/spray
P284 Wear respiratory protection
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves and clothing to prevent skin contact.
P273 Avoid release to the environment.
Response
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.
P370 + P378 In case of fire: Use Foam, alcohol foam, CO2, dry chemical for extinction.
P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.
P312 If inhaled, Call a POISON CENTER or doctor/physician if you feel unwell.
P314 Get medical advice/attention if you feel unwell

P302 + P352 IF ON SKIN: wash with plenty of soap and water
 P312 Call a POISON CENTER or doctor/physician if you feel unwell
 P361+P364 Take off immediately all contaminated clothing and wash it before reuse
 P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.
 P342 + P311 IF experiencing respiratory symptoms: call a POISON CENTER or doctor/physician.
 P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.
 P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 IF eye irritation persists: Get medical advice/attention.
 Storage:
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P233 Keep container tightly closed.
 Disposal:
 P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

HMIS Hazard Classification

HEALTH: 2 FLAMMIBILITY: 3 REACTIVITY: 1 PERSONAL PROTECTIVE EQUIPMENT: G

Potential Health effects

EYES: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING OR BLURRED VISION AS WELL AS CORNEAL OPACITY AND CONJUNCTIVITIS. SKIN: MAY CAUSE IRRITATION, DEFATTING, AND DERMATTITIS. SKIN ABSORPTION: CAN CAUSE REDDENING, SWELLING, RASH, SCALING OR BLISTERING. OVEREXPOSURE MAY CAUSE SENSITIZATION RESULTING IN REACTION TO CONTACT OF SMALL AMOUNTS. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. CAN CAUSE CORROSIVE ACTION TO MUCOUS MEMBRANES AND DIGESTIVE TRACTS. INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE NAUSEA AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, AND POSSIBLE UNCONSCIOUSNESS. BURNING SENSATION TO MUCOUS MEMBRANES, SHORTNESS OF BREATH AND FLU LIKE SYMPTOMS MAY OCCUR.

Health hazards (acute and Chronic)

CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. OVER-EXPOSURE TO THIS MATERIAL CAN CAUSE CARDIAC ABNORMALITIES. OVEREXPOSURE CAN POSSIBLY CAUSE ANEMIA. LIVER ABNORMALITIES, KIDNEY DAMAGE OR EYE DAMAGE. MAY CAUSE ASTHMA OR OTHER RESPIRATORY DISORDERS, BRONCHITIS, EMPHYSEMA, HYPERACTIVITY AND ECZEMA. CHRONIC INHALATION: AS A RESULT OF PREVIOUS REPEATED OVEREXPOSURES OR A SINGLE LARGE DOSE, CERTAIN INDIVIDUALS WILL DEVELOP ISOCYANATE SENSITIZATION (CHEMICAL ASTHMA), WHICH WILL CAUSE THEM TO REACT TO A LATER EXPOSURE TO ISOCYANATE AT LEVELS WELL BELOW THE TLV OR MGL. THESE SYMPTOMS, WHICH INCLUDE CHEST TIGHTNESS, WHEEZING, COUGH, SHORTNESS OF BREATH OR ASTHMA ATTACK, COULD BE IMMEDIATE OR DELAYED UP TO SEVERAL HOURS AFTER EXPOSURE. SIMILAR TO MANY NONSPECIFIC ASTHMATIC RESPONSES, THERE ARE REPORTS THAT ONCE SENSITIZED AN INDIVIDUAL CAN EXPERIENCE THESE SYMPTOMS UPON EXPOSURE TO DUST, COLD AIR, OR OTHER IRRITANTS. THIS INCREASED LUNG SENSITIVITY CAN PERSIST FOR WEEKS AND IN SEVERAL YEARS. CHRONIC OVEREXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING DECREASE IN LUNG FUNCTION, WHICH MAY BE PERMANENT. SENSITIZATION MAY EITHER BE TEMPORARY OR PERMANENT. ACUTE SKIN CONTACT: ISOCYANATES REACT WITH THE SKIN PROTEIN AND MOISTURE AND CAN CAUSE IRRITATION. SYMPTOMS OF SKIN IRRITATION MAY BE REDDENING, SWELLING, RASH, SCALING, OR BLISTERING. SOME PERSONS MAY DEVELOP SKIN SENSITIZATION FROM SKIN CONTACT. CURED MATERIAL IS DIFFICULT TO REMOVE. CHRONIC SKIN CONTACT: PROLONGED CONTACT WITH THE ISOCYANATE CAN CAUSE REDDENING, SWELLING, RASH, SCALING, OR BLISTERING. IN THOSE WHO HAVE DEVELOPED A SKIN SENSITIZATION, THESE SYMPTOMS CAN DEVELOP AS A RESULT OF CONTACT WITH VERY SMALL AMOUNTS OF LIQUID MATERIAL OR EVEN AS A RESULT OF VAPOR-ONLY EXPOSURE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
 RESPIRATORY CONDITIONS OR OTHER ALLERGIC RESPONSE.

CARCINOGENICITY

OSHA: NO NTP: NO IARC: YES

PRODUCT MAY CONTAIN ETHYL BENZENE AS A COMPONENT OF XYLENE (IARC 2B)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT | CAS NO. | OSHA PEL | ACGIH TLV | OSHA STEL | WEIGHT % |
|---|------------|----------|-----------|-----------|----------|
| Hopolymer of HDI | 28182-81-2 | 1 mg/m3 | NONE | NONE | 60-100 |
| *Xylene | 1330-20-7 | 100 PPM | 100 PPM | 150 PPM | 12 |
| *Ethyl benzene (as a component of xylene) | 100-41-4 | 100ppm | 100ppm | 125ppm | <2% |
| n-Butyl Acetate | 123-86-4 | 150 PPM | 150 PPM | 200 PPM | 7-13 |
| *Hexamethylene Diisocyanate (HDI) | 822-06-0 | NONE | .005 PPM | NONE | <1% |

*Indicates toxic chemical (s) subject to the reporting requirements of section 313 Title III and of 40 CFR 372. XYLENE ACGIH STEL= 150PPM.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

SECTION 4: FIRST AID MEASURES

| | |
|-------------------|---|
| Eyes | FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN. |
| Skin | FOR EXTREME EXPOSURE USE A SAFETY SHOWER IMMEDIATELY. WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY. |
| Ingestion | DO NOT INDUCE VOMITING. KEEP PERSON WARM AND CONSULT A PHYSICIAN IMMEDIATELY. GIVE 1-2 CUPS OR MILK OR WATER TO DRINK. |
| Inhalation | REMOVE VICTIM TO FRESH AIR AREA AND ADMINISTER OXYGEN IF NECESSARY. OBTAIN MEDICAL ASSISTANCE, ASTHMATIC TYPE SYMPTOMS MAY OCCUR IMMEDIATELY OR BE DELAYED FOR SEVERAL HOURS. TREATMENT IS SYMPTOMATIC. |

SECTION 5: FIRE FIGHTING MEASURES

| | |
|---|--|
| Suitable Extinguishing Media | FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL |
| Special Fire Fighting Procedures | DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. PRESENCE OF SOLVENTS IN PRODUCT MAY REQUIRE GROUNDING. REMOVE ALL SOURCES OF IGNITION. |
| Unusual Fire And Explosion Hazards | IF FIRE OCCURS, SOLVENTS MAY PRODUCE EXCESSIVE PRESSURE. SEALED DRUMS MAY RUPTURE AND IGNITE. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND AND IGNITE BY ANY SOURCE OF IGNITION. DURING A FIRE, HDI VAPORS AND OTHER TOXIC GASSES MAY BE EVOLVED. CONTAINERS MAY BURST IF CONTAMINATED WITH WATER. VAPOR FLASHBACK TO SOURCE IS POSSIBLE. FLAMMABLE LIMITS IN AIR, UPPER: N/A (% by volume) LOWER: N/A FLASH POINT: 91° +F METHOD USED: SETA FLASH |

SECTION 6: RELEASE MEASURES

| | |
|--|---|
| Steps To Be Taken In Case Material Is Released or Spilled | WEAR RESPIRATOR AND PROTECTIVE CLOTHING. REMOVE ALL SOURCES OF IGNITIONS. REMOVE EXCESS WITH SPARK PROOF EQUIPMENT, AND THE REMAINDER WITH AN ABSORBENT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. CONTAINED AIR RESPIRATOR MAY BE NECESSARY. |
|--|---|

SECTION 7: HANDLING AND STORAGE

| | |
|--|--|
| Precautions To Be Taken In Handling And Storage | STORE IN COOL DRY PLACE, SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING THE TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS. KEEP MATERIAL AWAY FROM ALL SOURCES OF IGNITION. |
| Other Precautions | AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CANNOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF. WEAR APPROPRIATE SAFETY EQUIPMENT AND RESPIRATOR AT ALL TIMES WHEN VENTILATION IS NOT SUFFICIENT TO CONTROL VAPORS. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE (29 CFR 1910.134). WHEN SPRAYING MATERIAL AVOID EXPOSURE TO ALL MISTS GENERATED BY USING AIR SUPPLIED RESPIRATOR. |

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| | |
|-------------------------------|---|
| Respiratory Protection | USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. ENGINEERING OR ADMINISTRATIVE MEASURES SHOULD BE TAKEN TO REDUCE THE RISK AND EXPOSURE. USE A POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR WHEN EXCEEDING TLV'S OR IF HDI MONOMER CONCENTRATIONS EXCEED ACCEPTABLE LIMITS OR WHEN SPRAYING MATERIAL. |
| Ventilation | EXHAUST VENTILATION SUFFICIENT TO KEEP AIRBORNE CONCENTRATIONS OF HDI BELOW THEIR TLV AND MGL MAXIMUM. REFER TO PATTY'S INDUSTRIAL HYGIENE AND TOXICOLOGY- VOLUME 1 (3RD EDITION) CHAPTER 17 AND VOLUME III (1ST EDITION) CHAPTER 3 FOR DETAILS. |

| | |
|---|--|
| Protective Gloves | IMPERVIOUS GLOVES – NEOPRENE OR RUBBER |
| Eye Protection | SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS. DO NOT WEAR CONTACT LENSES WHEN USING THIS PRODUCT. |
| Other Protective Clothing Or Equipment | WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS AN APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT. |
| Work Hygienic Practices | OBSERVE GOOD GENERAL HYGIENIC PRACTICES. SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES. |

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| | |
|---|---|
| Respiratory Protection | NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED. |
| Ventilation | AVOID BREATHING VAPORS. VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS. |
| Protective Gloves | IMPERVIOUS GLOVES – NEOPRENE OR RUBBER |
| Eye Protection | SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS. |
| Other Protective Clothing Or Equipment | WEAR BODY COVERING CLOTHING AND OTHER COVERINGS AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL. |
| Work Hygienic Practices | OBSERVE GOOD GENERAL HYGIENIC PRACTICES. SEE SECTION THREE FOR OCCPATONAL EXPOSURE LIMIT VALUES. |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---------------------------------------|
| Appearance And Odor | PALE YELLOW LIQUIDS WITH SOLVENT ODOR |
| Boiling Point Or Range | 279° F |
| Vapor Density | NOT AVAILABLE |
| Specific Gravity | 1.1 |
| Evaporation Rate | NOT AVAILABLE |
| Solubility In Water | NEGLIGIBLE |
| Odor Threshold | N/A |
| pH | N/A |
| Melting Point | N/A |
| Freezing Point | N/A |
| Vapor Pressure | N/A |
| Auto Ignition Temperature | N/A |
| Decomposition Temperature | N/A |
| Partition Coefficient: n-octanol/water: | N/A |

SECTION 10: STABILITY AND REACTIVITY

| | |
|--|---|
| Stability | STABLE |
| Condition To Avoid (Stability) | AVOID EXCESSIVE HEAT OR OPEN FLAMES AS WELL AS ALL SOURCES OF IGNITION SUCH AS SPARKS, HEATERS, STATIC DISCHARGES, ETC. |
| Incompatibility (Material To Avoid) | AVOID WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS, AND SURFACE ACTIVE COMPOUNDS. |
| Hazardous Decomposition | MAY FORM TOXIC CHEMICALS, CARBON DIOXIDE CARBON MONOXIDE, OXIDES OF NITROGEN, HCN AND HDI. |
| Hazardous Polymerization | MOISTURE OR MATERIALS THAT REACT WITH ISOCYANATES AND TEMPERATURES ABOVE 400 DEGREES F MAY CAUSE POLYMERIZATION. |

SECTION 11: TOXICOLOGICAL INFORMATION

| | |
|-----------------------|--|
| Component Data | Acute Oral Toxicity LD50 >5000 mg/kg (rat) (estimated value) Acute Inhalation Toxicity LC50 390-453 mg/m3, 4h (rat) Acute Dermal Toxicity LD50 >5000 mg/kg (rabbit) Skin Irritation, rabbit, Draize, slightly irritating Eye Irritation, rabbit, Draize, slightly irritating Sensitization: Dermal – Sensitizer (Guinea Pig, Maximization Test). Dermal – Non-Sensitizer (Guinea Pig, Buehler). |
|-----------------------|--|

Sensitization Inhalation – Non-sensitizer (Guinea Pig)
 Repeated Dose Toxicity: 3 wks, inhalation NOAEL: 3.7-4.3 mg/m³ (rat)
 Repeated Dose Toxicity: 90 d, inhalation NOAEL: 3.3-3.4 mg/m³ (rat)
 Repeated Dose toxicity: Irritation to lungs and nasal cavity
 Mutagenicity: Genetic Toxicity in Vitro, Ames: negative (salmonella typhimurium, metabolic Activation: with,without)
 COMPONENT n-Butyl Acetate: Acute oral LD50 > 5000 mg/kg (rat), Acute Inhalation Toxicity: LC50 > 23.4 mg/l, 4h (rat), Acute Dermal Toxicity LD50 > 5000 mg/kg (rabbit), Skin Irritation Guinea pig Acute Dermal Irritation exposure time 24h – Non-irritating, Skin Irritation Human patch test exposure time 48h – Non-irritating, Eye Irritation rabbit Draize exposure time 24h – slightly irritating, Sensitization dermal – non-sensitizing (guinea pig, human – maximization test). Repeated Dose Toxicity – 13 weeks inhalation NOAEL: 500 ppm (rat). Mutagenicity Genetic Toxicity in Vitro: Ames negative (Salmonella typhimurium, Metabolic Activation: with/without.
 COMPONENT Xylene: Inhalation LC50 26800ppm, Skin LD50 2000 mg/kg, Ingestion LD50 4.3 g/kg. Exposure may effect skin, eye, liver, kidney, nervous system, respiratory system and lungs. High concentrations may lead to nervous system effects. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal. Xylene may contain ethyl benzene.. Ethyl benzene has shown limited evidence of a carcinogenic effect.
 COMPONENT Ethyl Benzene: Acute Oral toxicity LD50: ca. 3500 mg/kg (rat); Acute inhalation LC50: 17.2 mg/l 4h (rat); Acute Dermal Toxicity: 17,800 mg/kg (rabbit); Skin Irritation rabbit Draize exposure time 24h – slightly irritating. Eye Irritation rabbit Draize – severely irritating. Sensitization dermal (human patch test) non-sensitizer. Repeated Dose toxicity 28 days inhalation NOAEL: 3.4 mg/l (rabbit). Mutagenicity Genetic Toxicity in Vitro: Ames: Negative (salmonella typhimurium, metabolic activation with/without). Carcinogenicity: Ethyl benzene was tested by inhalation exposure in mice and rats. In mice, there was an increased incidence of lung adenomas in males and liver adenomas in females. In male rats, there was an increased incidence of renal tubule adenomas and carcinomas. Two Studies of workers potentially exposed to ethyl benzene in a production plant and a styrene polymerization plant, showed no excess cancer incidence and no excess cancer mortality during a 15 year follow-up. Toxicity to Reproduction/Fertility: Inhalation (monkey, male) Reproductive effects have been observed in animal studies, In a generation study, inhalation (rat/female) NOAEL (parental): 100ppm NOAEL (F2): 100ppm. Developmental Toxicity/Teratogenicity rat, female, inhalation, gestation, daily, NOAEL (teratogenicity): 100ppm (maternal): 100ppm. Teratogenic effects seen only with maternal toxicity., Fetotoxicity seen only with maternal toxicity. Rabbit, female, inhalation, gestation, daily, NOAEL (teratogenicity) < 1000 mg/m³, NOAEL (maternal) < 1000 mg/m³.

SECTION 12: ECOLOGICAL INFORMATION

Component Data

COMPONENT Homopolymer of HDI: Biodegradation: 0%, Exposure time: 28 days, not readily biodegradable. Acute and Prolonged Toxicity to fish LC0 > 100 mg/l (zebra fish, 96 h). Acute toxicity to aquatic invertebrates: EC0 > 100 mg/l (water flea, 48 h). Toxicity to aquatic plants EC50 > 1000 mg/l (green algae, 72 h). Toxicity to Microorganisms: EC50 > 1000 mg/l (activated sludge microorganisms, 3 h).
 COMPONENT n-Butyl Acetate: Biodegradation: aerobic, 98%, exposure time 28 days. Biochemical oxygen demand (BOD) 1020 mg/g. Chemical Oxygen demand (COD) 2,320 mg/g. Bioaccumulation: ca. 4-14 BCF. Acute and Prolonged Toxicity to Fish LC50: 18 mg/l (fathead Minnow, 96 h). Acute Toxicity to Aquatic Invertebrate EC50: 72.8 mg/l (water flea, 48 h). Toxicity to aquatic plants EC50: 670 mg/l, end point: growth (Cryptomonad, 48 h). Toxicity to Microorganisms EC50: 959 mg/l (Pseudomonas putida, 48 h).
 COMPONENT Xylene: Acute Toxicity: Fish: Toxic 1 < LC/EC/IC50 < 10mg/l, Aquatic Invertebrates: Toxic 1 < LC/EC/IC50 < 10mg/l, Algae: Toxic 1 < LC/EC/IC50 < 10 mg/l. Mobility – floats on water. If it enters the soil it will be highly mobile and may contaminate groundwater. Oxidises rapidly by photo-chemical reactions in air.
 COMPONENT Ethyl Benzene: Biodegradation, Aerobic, 50%, Exposure time 28 days. Biochemical Oxygen demand (BOD) 5 days, 2.8% and 35 days, 1780 mg/g. Bioaccumulation: Cyprinus carpio (Carp), 15 BCF. Acute and Prolonged Toxicity to Fish LC50: 12.1 mg/l (fathead minnow, 96 h). Acute Toxicity to Aquatic Invertebrates EC50: 1.8-2.9 mg/l (water flea, 48 h). Toxicity to Aquatic Plants EC50: 4.6 mg/l (green algae, 72 h). Toxicity to microorganisms EC50: 130 mg/l (activated sludge microorganisms, 48 hr).

SECTION 13: WASTE DISPOSAL

Disposal Methods

DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS.

SECTION 14: TRANSPORT INFORMATION

DOT

UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTYL ACETATE), 3, PG III

IMO/IMDG

UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTYL ACETATE), 3, PG III

SECTION 15: REGULATORY INFORMATION

Component Data

Product: OSHA HAZCOM STANDARD RATING: Hazardous. All components on TSCA Massachusetts, New York, Pennsylvania Right to Know list includes the following components: Homopolymer of HDI CAS# 28182-81-2 @ 60-100%; n-Butyl Acetate CAS# 123-86-4 @ 10-20%; Xylene CAS# 1330-20-7 @ 7-13%; Ethyl Benzene CAS# 100-41-4 @ 1-5%. Massachusetts, New York, Pennsylvania Special hazardous Substance includes the following components: n-Butyl Acetate CAS# 123-86-4 @ 10-20%; Xylene CAS# 1330-20-7 @ 7-13%; Ethyl Benzene CAS# 100-41-4 @ 1-5%; hexamethylene diisocyanate (HDI) CAS# 822-06-0 @ <0.6%.

California Prop 65: This product contains chemicals known to the State of California to be carcinogenic: Ethyl Benzene CAS# 100-41-4 @ 1-5%.

US EPA CERCLA Hazardous Substances (40 CFR 302): n-butyl acetate reportable quantity 5000 lbs
US EPA CERCLA Hazardous Substances (40 CFR 302): Xylene reportable quantity 100 lbs.
US EPA CERCLA Hazardous Substances (40 CFR 302): Ethyl Benzene reportable quantity 1000 lbs.
US EPA Emergency Planning and Community Right to Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.5) components, Xylene and Ethyl Benzene.

SECTION 16: OTHER INFORMATION

DISCLAIMER: THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE AND IS BELIEVED TO BE ACCURATE, HOWEVER, THE MANUFACTURER MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF. ACCORDINGLY, WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THIS PRODUCT.

N/A = Not Available

See Section 1 for date of preparation